



GMS30KS-AU
33kVA Standby
27kW
30kVA Prime
24kW
Either 240v
Or 415v

Technical

Model	415v 240v	GMS30KS-AU PK30S-AU
Type		Heavy duty
Speed		1500RPM
Phase/Voltage		3-415 1-240
Frequency		50Hz
Standby Power		33kVA
Prime Power		30kVA
Noise Level Av (dba @ 7m)		58dbA
Fuel Capacity		100 L

Alternator

Manufacturer	Stamford
Model	PI144E
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Dimensions & Weight

Length	2.13m
Width	0.90m
Height	1.30m
Weight Dry	850Kg

240v set Outlets

Fitted—BUS connection point

415v set Outlets

Fitted—BUS connection point

Engine

Manufacturer	Kubota
Model	V3300-BG
Type	4 Stroke Diesel
Induction	Naturally Aspired
Fuel Consumption	6.6 L/hr @ 100% Load
Coolant Capacity	8.0L
Governor	Mechanical
Cubic Capacity	3.9 L
Oil Capacity	10 L

Controls

Controller	DSE Remote Auto Start
Circuit Breaker	RCD MCBO
Battery Isolator	Fitted
Battery Charger	Fitted

Canopy

Skid	Bunded fuel tank with tie down points and fork lift pockets
Canopy	Centre lift with lockable doors, Galvanized sheet, IP56* External Emergency Stop fitted.
Paint Finish	Heavy Duty Powder Coat White with Black base

Options

PMG Coolant Heater
Installation Service
Outlets