

EC Series

GMS200CS

— Generator Set Specification



Super Quiet, Superior Life!



GMS200CS



3-Phase, 50Hz@1500RPM				
	Voltage	kW	kVA	Amps
Prime Power	380	160	200	303.9
	400	160	200	288.7
	415	160	200	278.2
	440	160	200	262.4
Standby Power	380	177.8	222.2	337.6
	400	177.8	222.2	320.8
	415	177.8	222.2	309.2
	440	177.8	222.2	291.6
Noise Level at 7 meters (dBA)			69.5	

Notes:

- 1) Ambient reference conditions: 1,000 mbar, 27°C, 30% relative humidity;
- 2) Standby Power: the maximum power available under varying loads. Only for standby and emergency use. No overload is permissible. Prime Power: the maximum power available under varying loads for continuous operation. A 10% overload is permissible for 1 hour every 12 hours.

Features	Benefits
<ul style="list-style-type: none"> I Tightly structure, excellent design and craft I Designed with safety in mind I Earth leakage protection I Quick fix electrical power connections I Extensive option list I Well enclosed canopies with high protection against water and dust 	<ul style="list-style-type: none"> I Beautiful appearance I Low operating cost results in optimal economy I Ease of installation, operation, and maintenance I Customization I Good quality ensure

Performance Specification and Craftwork

Performance Specification		Telephone Interference, Electromagnetism	
Efficiency of Rated Power	96.3%	TIF	≤50
Time needed from start-up to full load (inductive)	125 seconds	THF	≤2%
Time needed from start-up to 50% load (inductive) allowed	8 seconds	Radio interference in compliance with BS800 and VED LEVELS G and N.	
1.1 times overload operation time (hour)	1	Craftwork <ul style="list-style-type: none"> • Steel base frame with AV mounting • standard 8h fuel tank with flexible rubber fuel tube, fuel level indicator and drainage • Overall sprayed powder coating • Whole set documents, including Installation Manual, Operation Manual, Spare Parts Catalog, Circuit Diagram Criterion <ul style="list-style-type: none"> • ISO3046, ISO8528, BS4999, BS5514, • BS5000PT99、AS1359, IEC34 • UTE5100, VDE0530 • ISO9001:2000 	
2.0 time overload operation time (minute)	1		
Voltage Regulation, steady state	≤±1%		
Voltage Regulation, transient state	20%-15%		
Voltage Settle Time	≤5 seconds		
Voltage Fluctuation Ratio	0.5%		
Frequency Regulation, steady state	±0.5% adjustable		
Frequency Regulation, transient state	±5%		
Frequency Settle Time	5 seconds		
Frequency Fluctuation Ratio	0.5%		
Recovery Time	0.5 seconds		

GMS200CS

Engine Specification			Alternator Specification	
Brand	Cummins		Brand	Stamford
Model	6CTAA8.3G2		Model	UCI274H
No. of Cylinders and Cycle	6L, 4 Stroke		Rated Output (kVA)	200
Induction System	TCA		Rated current (A)	288.7
Compression Ratio	16.8: 1		Exciter	Brushless
Displacement (L)	8.3		THF (BS EN60034- 1)	<2%
Bore x Stroke (mm)	114 x 135		Bearing number	Single
Torque (N.m)	1758		Windings	100% Copper
Speed RPM	1500		Connection Type	Star Connection
Piston speed (m/s)	6.8		Insulation Class	H
Air intake flow (L/s)	180		Winding Pitch	2/3
Exhaust flow (L/s)	422		Amortisseur Winding	Full
Net weight (kg)	684		A.V.R. Model	SX460, AS440
Starting System	Electronic		Voltage Regulation (no load- full load)	± 1.0%
Engine coolant flow (L/s)	3.3		Underspeed Protection	Standard
Base Output power (kW)	183		Protection	IP23
Fuel Consumption (L/h)	110% load		Phase Sequence	A(U), B(V), C(W)
	100% load	45.4	TIF (NEMA MG 1-22)	<50
	75% load	34	Excitation System	Self-excited, PMG optional
	50% load	23.3	Ambient Temp. (°C)	40
Governor Type	E		Stator Rated Temp. (°C)	125

Cooling System		Fuel System	
Max. coolant cycling resistance exterior engine (kPA)	28	Fuel injection pump model	pump with GAC governor
Thermostat adjusting temperature (°C)	83-95	Max. fuel input resistance of transfer pump (mmHg)	102
Min. opening pressure of radiator cap (kPA)	69	Max. overflow fuel resistance at overflow pipe of injector (mmHg)	254
Coolant capacity-engine only (L)	12.3	Total fuel overflow amount (L/h)	208
Exhaust System		Lubricating System	
Max. Back Pressure (kPA)	10.2	Normal oil pressure range	
Electrical System		Low idle (kPA)	103
Starter (V)	12/24	Rated speed (kPA)	276-414
Battery charging system (A)	63/40	Max. oil temperature permitted in oil pan (°C)	121
		Lubrication system Min. capacity (L)	23.8

GMS200CS

Control System

PLC-702

DSE-702 key manual start module is a manual engine control module designed to control the engine via a key switch and push buttons on the front panel. The module is used to start and stop the engine and indicate fault conditions, automatically shutting down the engine and giving a true first up fault condition of an engine failure.

Standard Control Function

- Manual Engine Control Module
- Low Oil Pressure
- High Engine Temperature
- Auxiliary Shutdown
- Overspeed Protection
- Protection hold-off timer
- Charge Failure warning




PLC-5220

DSE-5220 control panel is applied

- | Microprocessor control, with high stability and credibility
- | Mains supply and generator operation monitoring
- | Indicating operation status and fault conditions
- | Multiple protections; multiple parameters display, like pressure, temp.
- | Manual and automatic work mode selectable
- | Real time clock for time and date display, overall runtime display, 99 log entries
- | Overall power output display
- | Integral speed/frequency detecting, telling status of start, rated operation, overspeed
- | Communication with PC via RS485 OR RS232 interface, using MODBUS protocol.



Dimension and Weight



GMS200CS

Length × Width × Height, mm
3550×1300×1600

Weight (kg):
2548

GMS200CS

Optional

Engine	Alternator	Generator Set	Fuel System	Canopy
<ul style="list-style-type: none"> ● Coolant heater 	<ul style="list-style-type: none"> ● Space heater ● AVR PMG with regulator ● Anti-damp and anti-corrosion treatment ● Anti-condensation heater 	<ul style="list-style-type: none"> ● Tools with the machine 	<ul style="list-style-type: none"> ● Low fuel level alarm ● Automatic fuel feeding system 	<ul style="list-style-type: none"> ● Trailer ● Container
Lubricating System	Exhaust System	Cooling System	Control Panel	Voltages
<ul style="list-style-type: none"> ● Oil with the machine 	<ul style="list-style-type: none"> ● Protection board from hotness ● Low frequency silencer 	<ul style="list-style-type: none"> ● Front heat protection ● 50°C radiator ● Coolant (-30°C) 	<ul style="list-style-type: none"> ● Remote control panel ● Automatic paralleling control panel ● Automatic Transfer Switch (ATS) 	<ul style="list-style-type: none"> ● 415/240V ● 400/230V ● 380/220V ● 220/127V ● 200-115V



Local Distributor