

# AG30KS-AU 30kVA 3PHASE



## Dependable Power

**Kubota Diesel** 

**Stamford Alternator** 

**Deep Sea Control** 

### Technical

Model	AG30KS-AU
Type	Heavy duty
Speed	1500RPM
Phase/Voltage	3-240/415
Frequency	50Hz
Standby Power	33kVA
Prime Power	30kVA
Noise Level (dba @ 7m)	70dba
Fuel Capacity	180 Litres

### Engine

Manufacturer	Kubota
Model	V3300-BG
Type	4 Stroke Diesel
Induction	Naturally Aspired
Fuel Consumption	707 L /hr @ 100% Load
Coolant Capacity	8.2L
Governor	Mechanical
Cubic Capacity	3.9 L
Oil Capacity	13.2 L

### Alternator

Manufacturer	Stamford
Model	UC1224D
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

### Controls

Controller	Deep Sea 702
Circuit Breaker	Two Pole RCD MCBO
Battery Isolator	Fitted adjacent to the battery

### Dimensions & Weight

Length	2.34m
Width	1.05m
Height	1.55m
Weight Dry	1310Kg

### Canopy

Skid	Bunded fuel tank with tie down points and fork lift pockets
Canopy	Centre lift with lockable doors, Galvanized sheet, External Emergency Stop fitted.
Paint Finish	Heavy Duty Powder Coat White with Black base

### Outlets

Outlets 3 phase	20amp IP66 with CB
Outlets 1 phase	3 x 15amp IP66 with RCD MCBO

### Options

PMG Battery Charger	Block Heater	Auto Start
Installation	Service	

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.