

PK30KS1-AU 30kVA SINGLE PHASE



Dependable Power

Kubota Diesel 

Stamford Alternator 

Deep Sea Control 

Technical

Model	PK30KS1-AU
Type	Heavy duty
Speed	1500RPM
Phase/Voltage	1-240
Frequency	50Hz
Standby Power	33kVA
Prime Power	30kVA
Noise Level (dba @ 7m)	58dba
Fuel Capacity	100 L

Engine

Manufacturer	Kubota
Model	V3300-BG
Type	4 Stroke Diesel
Induction	Naturally Aspired
Fuel Consumption	6.6 L @ 100% Load
Coolant Capacity	8.0L
Governor	Mechanical
Cubic Capacity	3.9 L
Oil Capacity	9.7 L

Alternator

Manufacturer	MECCALTE
Model	ECP28-VL/4
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Controls

Controller	Deep Sea 4510
Circuit Breaker	Two Pole MCB
Battery Isolator	Fitted adjacent to the battery

Dimensions & Weight

Length	2.59m
Width	1.1m
Height	1.7m
Weight Dry	1375Kg

Canopy

Skid	Bunded fuel tank with tie down points and fork lift pockets
Canopy	Centre lift with lockable doors, Galvanized sheet, External Emergency Stop fitted.
Paint Finish	Heavy Duty Powder Coat White with Black base

Outlets

BUS only

Options

PMG Battery Charger Block Heater Auto Start Installation Service

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.